M73ES

Utilizzo: servizio commerciale
Use: commercial service

EFFICIENZA STANDARD
STANDARD EFFICIENCY

Argano per scale mobili installate in ambienti commerciali quali: grandi magazzini, centri commerciali multipiano, cinema multisala, hotel ecc..

Traction machine for escalators installed in commercial buildings such as: department stores, multi-storey shopping centers, multiplex cinemas.hotels etc..

Caratteristiche/Features:

- Idonea all'utilizzo continuo: struttura alettata per la dissipazione del calore.
- Flangiatura e albero con dimensioni standard, compatibili con i motori in commercio.
- L'albero lento si adatta ai pignoni per catena standard.
- Uscita albero: destra o sinistra.

- *Suitable for continuous use: ribbed frame that allows heat dissipation.*
- *Flange and shaft with standard dimensions, compatible with the motors on the market.*
- *Slow shaft easy to fit in pinions for standard chain.*
- *Output shaft: right or left.*



M73ES

dati tecnici
technical data

Versione	Rapporto	Vel. uscita	Momento torc. max.	Potenza	Rendimento (1)	Peso
Version	***Ratio***	***Output speed***	***Max torque***	***Power***	**Efficiency**	***Weight***
		RPM	Nm	kW	**Full load**	kg
M73ES-5.5-6P	24.5	39.18	1099	5.5	**0.85**	285
M73ES-7.5-6P	24.5	39.18	1499	7.5	**0.85**	295

(1) solo argano - only gearbox

Efficienza oltre
Efficiency more than

80%



Disegno tecnico con uscita albero a destra
Technical drawing with right output shaft

NOTE - ***NOTES***	
Protezione - *Protection*:	IP55
Temperature ambiente - *Ambient temperature*:	max 40 °C
Olio sintetico - *Synthetic oil:*	ISO VG460
Freno - *Brake:*	2 x 140 Nm

GRUPPO FRENO - ***BRAKE SYSTEM***	
Tipo - *Type*	Start / hold V
Dati - *Data*	207/104 V_{DC} S1 1,12/0,56 A - 232/116 W - 185 OHM
Scheda alimentazione Booster 230 V_{AC} *Booster power board 230 V_{AC}*	

ACCESSORI - ***OPTIONAL***	
Sensore di rotazione - *Rotation Sensor:*	PNP or NPN
Sensore di usura - *Wear Sensor:*	24V DC 1A
Microcontatto freno - *Brake Microswitch:*	NO – NC AC15 2A / 250V DC13 0.25A / 250V

Rev. 12 - 03_2023